

ET-LED 96 x 16 RGY (P-ET-A-00522)



ET-LED 96x16 RGY is all-purpose moving sign display board that uses 3-colored LED that is red, green, and yellow. It can display both Thai and English letters or all languages that are supported by OS WINDOWS. It can program text from PORT RS232 or USB FLASH DRIVE from computer PC easily; it is suitable for shops to advertise products and service publicly.

Moreover, ET-LED 96x16 RGY can be applied to be 6-gigit Clock, or show temperature and humidity measurement. (NOTE: Sensor is OPTION, user must order separately).

- Display is LED type that is 96cm in width and 16cm. in height. It is red LED and green LED; so, it can display data by 3 colors; red, green, yellow.
- Resolution is 96 x 16 DOT (1 DOT consists of 1 red LED and 1 green LED)
- Brightness of Display is 3500 CD/M2 that can be obviously seen for a long-distance
- Provide internal RTC with BATTERY 3V to show time
- There are 2 ways to edit and change text on Display; via RS232 PORT, it is directly connected with computer PC; or, via USB FLASH DRIVE, it programs and writes data into FLASH DRIVE on computer PC and remove to connect with Connector USB on ET-LED to auto LOAD text.
- Can show text in all languages that are supported by WINDOWS
- Program and write text on WINDOWS 98SE/ME/2000/XP/7/8/8.1
- Can write 200 programs to command and display data that supports the format of TEXT, GIF, JPG, JPEG, BMP and etc.
- Use 220VAC/50Hz Power Supply; it only uses indoors; it does not suggest to use outdoors.
- Board size: 103cm in width x 23cm in height x 9cm in thickness. It is made of black aluminum with 6.00kg in weight.
- Display size: 96cm in width and 16cm in height
- Package of ET-LED 96 x 16 RGY consists of...
  1. Sign Board ET-LED 96 x 16 RGY
  2. CABLE AC LINE 5M
  3. CABLE RS232 5M
  4. CD-ROM Manual, Program and Example Programs.

CONNECTOR for connecting with PROBE SENSOR Temperature, Humidity (NOTE: Sensor is OPTION, user must order separately).

There are 2 ways to edit and change text on Display; via RS232 PORT, it is directly connected with computer PC; or, via USB FLASH DRIVE.

Board Controller of ET-LED 96x16 RGY is installed internal the box.



OPTION ชื่อเพิ่มเติมการทำงาน

• PROBE DS18B20 LED 1M (P-ET-A-00523)



This PROBE is connected with ET-LED 96x16; it is IC No.DS18B20 with Cable is 1 meter in length. It is Connector STAINLESS type, water proof that measures temperature and shows data on ET-LED 96x16.

• PROBE AM2301 LED 20CM (P-ET-A-00524)



This PROBE is used with ET-LED 96x16; it is IC No.AM2301 with Cable is 20cm. in length that measures temperature and humidity and shows data on ET-LED 96x16.